




ALLAMERICANALARM.COM 239.334.7447

VB-DVR-8-500GB

PRODUCT FEATURE

- * H.264 Hardware Video Compression (120 PPS)
- * Support CMS (Central Management System)
- * Audio Backup / Audio Streaming.
- * Support Google Android™, iPhone™, BlackBerry™, 3GPP Support
- * IRC (IE Remote Control): User Can Setup DVR from IE Browser
- * Support time-point backup function under Ethernet remote control mode.
- * User can select any time period to process backup from remote side.
- * Support time-search & event-search function under Ethernet remote control mode.
- * Support PPPoE/Static/DHCP IP & DDNS
- * Real Triplex, recording/ live-time & playback operation at the same time available.



PRODUCT SPECIFICATION

VIDEO	
MODE	Triplex
IMAGE SYSTEM	NTSC PAL
LIVE-TIME RESOLUTION	720x480 720x576
LIVE-TIME DISPLAY RATE	4 x 30 Frame / Sec 4 x 25 Frame / Sec
SPLIT SCREEN	1, 4
VIDEO INPUT	BNC x 4
VIDEO OUTPUT (BNC)	BNC x 1
VIDEO OUTPUT (VGA)	Yes
AUDIO	
AUDIO INPUT	RCA x 1
AUDIO OUTPUT	RCA x 1
AUDIO BACKUP	Yes
AUDIO STREAMING	Yes
RECORDING	
COMPRESSION TYPE	H.264
RECORDING RESOLUTION (D1)	720x480 720x576
RECORDING RESOLUTION (HALF D1)	720x240 720x288
RECORDING RESOLUTION (CIF)	360x240 360x288
RECORDING RATE (D1)	720 x 480 up to 30 PPS 720 x 576 up to 25 PPS
RECORDING RATE (HALF D1)	720 x 240 up to 60 PPS 720 x 288 up to 50 PPS
RECORDING RATE (CIF)	360 x 240 up to 120 PPS 360 x 288 up to 100 PPS
COMPRESSION RATE	Low : 1 K Bytes Medium : 2.2 K Bytes High : 3.2 K Bytes Best : 6 K Bytes
RECORDING MODE	Manual / Schedule / Alarm
PLAYBACK & SEARCH	
PLAYBACK SPEED	Fast Forward X 2 X 4 X 8 Fast Backward X 2 X 4 X 8 field by field Playback Pause
TIME SEARCH	Yes
EVENT SEARCH	Yes
EVENT LIST	3000 records per H.D.D (Maximum)
OSD & CONTROL INTERFACE	
TITLE	8 Characters
ON SCREEN DISPLAY & SETUP	Time / Date / Setup Menu
GRAPHIC USER INTERFACE (GUI)	Yes
DVR CONTROL PANEL	Yes
MOUSE	Yes
IR REMOTE CONTROLLER	Yes

OSD & CONTROL INTERFACE	
IE BROWSER	Yes
PLAYER	Yes
STORAGE & BACKUP DEVICE	
INTERNAL HDD SUPPORT	SATA HDD x 1
EXTERNAL USB HDD SUPPORT	Yes
USB PAN DRIVE BACKUP	Yes
NETWORK	
ETHERNET	Yes
ETHERNET COMPRESSION FORMAT	H.264
IE REMOTE CONTROL	Yes
DDNS	Yes
NTP	Yes
E-MAIL & FTP	Yes
NETWORK IP	Static/ Dynamic/ PPPoE
MULTI-REMOTE CLIENT	Yes (4 Clients at the same time available)
PDA/ CELL PHONE SUPPORT	Yes (MPEG4)
3GPP	Yes (MPEG4)
ALARM	
ALARM INPUT	4 In (NO/NC)
ALARM OUTPUT	1 Out (NO/NC)
MOTION DETECTION	Yes
MOTION DETECTION AREA	30 x 24 grids
MOTION DETECTION SENSITIVITY	1-100
VIDEO LOSS DETECTION	Yes
ALARM RECORDING	Yes
BUZZER	Yes
SETUP & OTHER FUNCTIONS	
DAYLIGHT SAVING TIME	Yes
PTZ CONTROL	Yes
RS-485	Yes
DIGITAL ZOOM	Yes
PASSWORD CONTROL	Two levels, one for system and the other for HDD format
KEY-LOCK	Yes
MULTI-LANGUAGE	Yes
FIRMWARE UPDATE	USB Host & Update on line
OTHERS	
POWER INPUT	DC 12V
DIMENSIONS (W x H x D)	218mm x 44mm x 202mm
WEIGHT (kg)	1.4 kg